# BEST AVAILABLE COPY

Hawley's

Condensed Chemical

Dictionary

THIRTEENTH EDITION

Revised by

Richard J. Lewis, Sr.



JOHN WILEY & SONS, INC.

New York • Chichester • Weinheim • Brisbane • Singapore • Toronto

## **BEST AVAILABLE COPY**

This text is printed on acid-free paper.

Copyright © 1997 by John Wiley & Sons, Inc.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning or otherwise, except as permitted under Sections 107 or 108 of the 1976 United States Copyright Act, without either the prior written permission of the Publisher, or authorization through payment of the appropriate per-copy fee to the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, (978) 750-8400, fax (978) 750-4744. Requests to the Publisher for permission should be addressed to the Permissions Department, John Wiley & Sons, Inc., 605 Third Avenue, New York, NY 10158-0012, (212) 850-6011, fax (212) 850-6008, E-mail: PERMREQ@WILEY.COM.

### Library of Congress Cataloging-in-Publication Data

Condensed chemical dictionary.

Hawley's condensed chemical dictionary.—13th ed./revised by Richard J. Lewis, Sr.

ISBN 0-471-29205-2 (hardcover)

1. Chemistry-Dictionaries. I. Hawley, Gessner Goodrich, 1905-1983.

II. Lewis, Richard J., Sr. III. Title.

QD5.C5 1997

540'.3-dc21

97-35762

Printed in the United States of America

10 9 8 7 6 5 4 3 2

h

th

į۷,

iic

οr

ıle

m.

ies

·ad

(4)

⊕f

g

19

. · X -

thin-laver chromatography. (TLC). A micro type of chromatography. The thin layer (0.01 inch) is the adsorbent, usually a special silica gel spread on glass or incorporated in a plastic film. Single drops of the solutions to be investigated are placed along one edge of the glass plate, and this edge then dipped into a solvent. The solvent carries the constituents of the original test drops up the thin layer in a selective separation, so that a comparison with known standards and various identifying tests may be made on the spots formed. See thin.

thinner. A hydrocarbon (naphtha) or oleoresinous solvent (turpentine) used to reduce the viscosity of paints to appropriate working consistency usually just before application. In this sense a thinner is a liquid diluent, except that it has active solvent power on the dissolved resin.

thio. A prefix used in chemical nomenclature to indicate the presence of sulfur in a compound, usually as a substitute for oxygen. See thiol.

#### thioacetamide.

CAS: 62-55-5. CH<sub>1</sub>CSNH<sub>2</sub>.

Properties: Colorless leaflets. Mp 115C. Stable in solution. Soluble in water, alcohol, ether, benzene. Combustible.

Hazard: Toxic by ingestion and inhalation, a carcinogen (OSHA).

Use: To replace gaseous hydrogen sulfide in qualitative analysis.

thioacetic acid. (thiacetic acid: ethanethiolic acid).

CAS: 507-09-5. CH, COSH.

Properties: Clear, yellow liquid; strong, unpleasant odor. D 1.05 (25C), fp -17C, bp 81.8C (630 mm Hg). Soluble in water, alcohol, and ether. Combustible.

Derivation: By heating glacial acetic acid and phosphorus pentasulfide, with subsequent distillation. Hazard: Toxic by ingestion and inhalation.

Use: Chemical reagent, lachrymator.

thioallyl ether. See allyl sulfide.

thioanisole. C, H, CH,.

Properties: Colorless liquid; strong, unpleasant odor. D 1.053 (25C), fp -15.5C, bp 188C, refr index 1.5842 (25C). Insoluble in water; soluble in most organic solvents. Combustible.

Use: Intermediate, solvent for polymeric systems.

#### thiobenzoic acid. C<sub>6</sub>H<sub>5</sub>COSH.

Properties: Yellow oil or crystals. D 1.1825-1.1835 (20/4C), mp 24C, bp 77.5C (5 mm Hg), 122C (30 mm Hg), refr index 1.602-1.604 (20C). Insoluble in water; miscible with organic solvents. Combustible.

Grade: 95% min. Use: Organic intermediate.

#### 4,4'-thiobis(6-tert-butyl-m-cresol).

CAS: 96-69-5.

Properties: Light-gray to tan powder. Mp 150C min. d 1.10 (25C).

Hazard: Toxic by inhalation. TLV: 10 mg/m<sup>3</sup> of air. Use: Protection of light-colored rubber from oxidation and of nonstaining neoprene compounds against deterioration.

#### 2,2'-thiobis(chlorophenol).

CAS: 97-18-7. [CIC, H<sub>3</sub>(OH)]<sub>2</sub>S.

Properties: White, crystalline solid: odorless. Mp 175.8-186.8C. Insoluble in water.

Hazard: Toxic by ingestion.

Use: Bacteriostat for cosmetics, fungicide.

#### 2,2'-thiobis(4,6-di-sec-amylphenol).

(2,2'-thiobis[4,6-bis-(1-methylbutyl)phenol]).

[(CH,[CH,],CH[CH,]),OHC,:H,],S

Properties: A dark, viscous liquid. Softening p 0C. d 0.99 (50C).

Use: Rubber antioxidant.

thiocarbamide. See thiourea.

thiocarbanil. See phenyl mustard oil.

thiocarbanilide. (N,N'-diphenylthiourea: sulfocarbanilide).

CAS: 102-08-9. CS(NHC,H,)...

Properties: Gray powder. Mp 148C. d 1.32. Soluble in alcohol and ether; insoluble in water. Combustible.

Derivation: Interaction of aniline and carbon disulfide and alcohol in the presence of sulfur.

Use: Intermediates, dyes (sulfur colors, indigo. methyl indigo), vulcanization accelerator, synthetic organic pharmaceuticals, flotation agent, acid inhibitor.

thiocarbonyl chloride. See thiophosgene.

thioctic acid. See dl- $\alpha$ -lipoic acid.

thiodiethylene glycol. See thiodigylcol.

thiodiglycol. (thiodiethylene glycol:

 $\beta$ -bis-hydroxyethyl sulfide; dihydroxyethyl sulfide). (CH2CH2OH)2S.

Properties: Syrupy, colorless liquid: characteristic odor. D 1.1852 (20C), bp 283C, fp -10C, viscosity 0.652 cP (20C), flash p 320F (160C), bulk d 9.85 lb/gal, refr index 1.5217 (20C). Soluble in acetone. alcohol, chloroform, water; slightly soluble in benzene, carbon tetrachloride, and ether. Combustible.

Derivation: Hydrolysis of dichloroethyl sulfide, interaction of ethylene chlorohydrin and sodium sul-

Hazard: Do not use with hydrochloric acid.

ituithtals :m). . are ı on ·mic tely ery

:es